

TUG TECHNOLOGIES

Providing Ground Support Solutions Worldwide



Model shown above includes additional options.

TUG 660 Belt Loader Featuring the Kubota Engine

With the heaviest chassis in its class, the TUG 660 belt loader assures years of dependable service in the most demanding ramp applications. The central mounted conveyor is elevated at both ends by lift arms that are activated by single-stage, double-acting cylinders. The front of the conveyor operates at heights between 40 and 170 inches (1.02 and 4.32 m) while the height at the rear of the unit can be adjusted between 13 and 37 inches (0.33 and 0.94 m). The unit is equipped with belt controls operable from either end of the conveyor and an interlock prevents the engine throttle from being advanced for adjustment of belt speed unless the Direction Control is in neutral. A guide on each side of the conveyor assembly can be retracted if a clear conveyor surface is required. A collapsible safety rail is fitted on the side of the conveyor and an emergency hydraulic pump is standard equipment.

Kubota engines are so reliable that they offer a 3 year/ 3,000 hour warranty, that is one of the best in the business. Emissions are also not a problem because this engine is Tier III compliant and is interim Tier IV. Which means that the engine is compliant until 2012!

Equipment Sales
Tel: (770) 422-7230
Fax: (770) 428-7315

Parts Sales
Tel: (800) 989-8499
Fax: (770) 422-8730

Online
www.tugtech.com

*New In 2008:
TUG 660 Powered by
Kubota*

- Kubota Engine Warranty 3 years/3,000 hours
- Tier III compliant until 2012
- Economic Fuel Ratings
- Outstanding Reliability
- Extensive dealer networks domestically/ internationally
- Standard Hydro-Boost braking system
- One side service



If it doesn't say TUG, it's not TUG TUFF

